WOODS LEWBLADES AND RAKES

REAR BLADES

Ideal for grading dirt or gravel, cleaning up construction sites and moving snow

- Formed moldboard made from high-strength steel provides exceptional rigidity and pivots 360°
- Reversible, bolt-on cutting edge adds to product life and enables easy replacement
- Tilt and offset functions for advanced grading applications (premium models)
- Fast, easy, and safe hook-ups with ASAE Quick Hitch compatibility
- Optional skid shoes for depth control, optional parking stand for easier attachment, and optional end plates (premium models) for moving more material



LANDSCAPE RAKES

Ideal for lawn maintenance projects and clearing debris at construction sites



- Heavy pivot components increase product longevity
- Large, structural tine beam channel holds alloy spring steel tines firmly
- Fast, easy and safe hook-ups with ASAE quick-hitch compatibility
- Optional gauge wheels allow better depth control and optional parking stand for easier attachment




Woods Rear Blades

Specifications	RBS54	RBS60	RBS72	RBS60P	RBS72P	RBS84P		
Tractor Engine HP		up to 30 hp		20-45 hp				
Tractor Hitch	I	Limited Cat 1 and	1	Cat 1				
Working Width	54"	60"	72"	60"	72"	84"		
Approximate Weight	134 lbs	142 lbs	156 lbs	268 lbs	288 lbs	308 lbs		
Moldboard Height		12"		15"				
Moldboard Thickness	3.	/16" (grade 80 stee	el)	1/4" (grade 80 steel)				
Reversible Cutting Edge Dimensions		3/8" x 6"		1/2" x 6"				
Pivot Angle	Forward - 5 @ 15°, Reverse - 5 @ 15°							
Tilt	_	_	_	up to 15°				
Offset	_	_	_	up to 12" left or right				
End Plates	_	_	_	optional				
Skid Shoes	optional							
ASAE Quick Hitch Compatible	yes							
Parking Stand	optional							
	Standard-duty			Standard-duty (Premium)				

Woods Landscape Rakes

Specifications	LRS52	LRS60	LRS72	LRS72P	LRS84P	LRS96P			
Tractor Engine HP		up to 30 hp		20-45 hp					
Tractor Hitch	L	imited Cat 1, Cat	1	Cat 1					
Working Width	52"	60"	72"	72"	84"	96"			
Approximate Weight	156 lbs	168 lbs	186 lbs	264 lbs	288 lbs	311 lbs			
Pivot Angle	Forward - 5 @ 15°, Reverse - 5 @ 15°								
Tine Dimensions	5/16" x 1"								
Tines Spacing	1"								
Gauge Wheels	optional								
ASAE Quick Hitch Compatible	yes								
Parking Stand	optional								
	Standard-duty Standard-duty (Premium)								



Woods Equipment Company

RBS72 Rear Blade

Woods Equipment A Blount International Company

2606 South Illinois Route 2, Oregon, Illinois 61061 tel 800-319-6637 woodsequipment.com

Warning! Some images may show safety shields removed to provide a better view. Equipment should never be operated with any safety shield removed. Some machines in this brochure may be shown with optional equipment. Always operate machines in accordance with supplied operator's manuals. ©2014 Woods Equipment Company, All rights reserved. WOODS and Woods logo are trademarks of Woods Equipment Company. All rights reserved in this brochure are the property of their respective companies or mark holders. Specifications subject to change without notice.

B051401 May 2014 Printed in the USA